

## China Sanew Cable Co., Ltd.

#### Fiber Glass Braid Silicone Rubber High Temperature Wire


#### **Product Features:**

This product is subject to the specification that manufacture with silicone rubber over which is fabricated with glass yarn coated with heat-resistant specific varnish.

It is superior to heat-resistance, cold-resistance, durability, and electric insulation use for various kinds of sector; internal wiring, automobile, vessel, illuminator, heater and air-conditioner.

#### The applications:

Applicable for high temperature environment such as electron, electrical household appliance, lamps and lanterns, combustion equipment and internal wiring of electronic equipment.



#### TECHNICAL DATA:

Min. bend radius for installation: 10 x cable diameter

Temperature range: -60°C to +180°C

**7** Working Voltage: 300V **1500V 1500V** 

**Conductor stranding:** Multi-piece or single piece Tin-ed, nickel-plated

or silver-plated copper wire

Color Code: According to Clients

Approvals: According to UL 758, UL1581 UL VW-1

Add: 2-1-101, Binhefang, Daxing District, Beijing, China Zip: 102600 Tel: +8 6 - 10 -5 1265801

E-mail: international@sanew-cable.com Fax: +86 - 10 -51286576



# China Sanew Cable Co., Ltd.

### Fiber Glass Braid Silicone Rubber High Temperature Wire

Conductor		Insulation Nominal thickness		Nominal Diameter		Max
		mm		mm		resistance
Nominal area	Structure of	300/300V	300/500V	300/300V	300/500V	20°C Ω/km
mm <sup>2</sup>	conductor					
	No./mm					
0.14	8/0.15	0.4	0.6	2.2	2.6	143
0.20	12/0.15	0.4	0.6	2.3	2.8	95.0
0.30	16/0.15	0.4	0.6	2.4	2.9	71.2
0.40	23/0.15	0.4	0.6	2.6	3.0	49.6
0.50	16/0.20	0.4	0.6	2.7	3.2	40.1
0.75	24/0.20	0.4	0.6	3.0	3.5	26.7
1.0	32/0.20	0.4	0.6	3.2	3.7	20.0
1.5	30/0.25	0.4	0.7	3.6	4.3	13.7
2.5	50/0.25	0.5	0.8	4.3	5.0	8.21
4	56/0.30	0.5	0.8	4.9	5.6	5.09
6	84/0.30	0.5	0.8	6.3	7.0	3.39
10	84/0.40	0.6	1.0	8.0	8.9	1.95
16	126/0.40	0.6	1.0	9.2	10.2	1.24

Add: 2-1-101,Binhefang, Daxing District ,Beijing ,China Zip: 102600 Tel: +8 6 - 10 -5 1265801 E-mail: <a href="mailto:international@sanew-cable.com">international@sanew-cable.com</a> Fax: +86 - 10 -5 1286576